



BGx 542 HP




BGx 663 HP




BGx 693 HP

	BGx 402 HP	BGx 542 HP	BGx 663 HP	BGx 693 HP
System	2-way Coaxial	2-way Coaxial	3-way Triaxial	3-way Triaxial
Diameter	100 mm	130 mm	165 mm	6 x 9"
Rated power	30 watts	40 watts	50 watts	55 watts
Peak power	130 watts	170 watts	210 watts	240 watts
Sensitivity 2,83 V/m	90 dB	91 dB	93 dB	92 dB
Frequency response	90 – 20.000 Hz	70 – 20.000 Hz	40 – 22.000 Hz	40 – 22.000 Hz
Impedance	4 ohms	4 ohms	4 ohms	4 ohms
Cone material	Injected PP	Injected PP	Injected PP	Injected PP
Installation depth	39,5 mm	48 mm	56 mm	73 mm



IC 107



IC 118



IC 115



IC 109

	IC 102	IC 104	IC 107	IC 109	IC 118	IC 112	IC 115	IC 122
System	Dual Cone	Dual Cone	Dual Cone	Dual Cone	Dual Cone	2-way Coaxial	2-way Coaxial	2-way Coaxial
Diameter	100 mm	100 mm	130 mm	4 x 6"	165 mm	100 mm	130 mm	35 mm
Rated power	20 watts	20 watts	25 watts	25 watts	30 watts	25 watts	30 watts	105 watts
Peak power	60 watts	60 watts	75 watts	75 watts	90 watts	75 watts	90 watts	260 watts
Sensitivity 2,83 V/m	90 dB	90 dB	91 dB	91 dB	91 dB	91 dB	91 dB	91 dB
Frequency response	55 – 20.000 Hz	55 – 20.000 Hz	55 – 22.000 Hz	55 – 20.000 Hz	50 – 20.000 Hz	55 – 22.000 Hz	55 – 22.000 Hz	50 – 22.000 Hz
Impedance	4 ohms	4 ohms	4 ohms	4 ohms	4 ohms	4 ohms	4 ohms	4 ohms
Cone material	Injected PP	Injected PP	Injected PP	Injected PP	Injected PP	Injected PP	Injected PP	Injected PP
Installation depth	41 mm	41,5 mm	45,7 mm	47,4 mm	54,7 mm	41,5 mm	45,5 mm	54,7 mm